



## IKA... (CBA...)

SUPPORTO 180°  
ISO 8132  
100-250 bar  
MATERIALE: EN-GJS 500/7

BRACKET 180°  
ISO 8132  
100-250 BAR  
MATERIAL: EN-GJS 500/7



SIGLA ARTICLE	B	E	E1	G (H9)	H	H1	N	N1	R1	R	S	FORZA NOMINALE RATED VALUE	PESO IN Kg. WEIGHT Kg.
												KN.	
IKA 10	24	33	60	10	32	22	17	42	10	6.6	10	5	0.1
IKA 12	28	40	70	12	34	22	20	50	12	9	12	8	0.31
IKA 16	36	50	90	16	40	27	26	65	16	11	16	12.5	0.59
IKA 20	45	58	98	20	45	30	32	75	20	11	20	20	0.9
IKA 25	56	70	113	25	55	37	40	85	25	13.5	25	32	1.6
IKA 32	70	85	143	32	65	43	50	110	32	17.5	32	50	2.8
IKA 40	90	108	170	40	76	52	65	130	40	22	40	80	5.0
IKA 50	110	130	220	50	95	65	80	170	50	26	50	125	10.1
IKA 63	140	160	270	63	112	75	100	210	63	33	63	200	15.4
IKA 80	170	210	320	80	140	95	125	250	80	39	80	320	30.0
IKA 100	210	260	400	100	180	120	160	315	100	45	100	500	60.2